

Affordable CCTV solutions.

Compact Series: 1080p fixed lens IP surveillance kits available in 4 channels

The Watchguard[™] fixed lens surveillance kits are high performance CCTV systems for an affordable price. These CCTV kits offer broadcast-quality image performance with built-in PoE and they are ideal for any home or business.

- Records Full HD 1080p (1920 x 1080) up to real-time 50fps
- 1080p True WDR 50m IR dome cameras in 3.6mm
- Low light colour footage at 0.009lx min. illumination
- IVS with tripwire, intrusion, motion detection & more
- IP67 rated, metal housing cameras for outdoor use
- Remote view in seconds with setup via QR code
- Built-in Power over Ethernet or power via 12VDC
- Pre-installed 1TB surveillance grade HDD
- Remote view for iOS, Android & Windows Phone *Camera cabling sold separately



Comprehensive, ready to install packages.

The Watchguard[™] Compact Series offers a complete 4 channel network surveillance package, purpose-built for rapid installation and impressive results.

Kit Model	NVRKIT-C421F
Kit Image	
Network Video Recorder	NVR4COM2 with 4 Port PoE & 1 x SATA Bay
Internal Storage	1TB Surveillance HDD
Standard Cameras	4 x VSIPE2MPVDMINIIRCB3.6 1080p True WDR 50m IR Turret Dome
Included Accessories	1 x 1.5m CAT5 patch cable for networking / 1 x 1m HDMI output cable / 1 x NVR Remote and 1 x Mouse *Camera cabling sold separately

Kit Specifications

For full specifications and bracket compatibility, please see the individual product web entry or datasheet.

NVR Model	NVR4COM2
Product Image	
Video Input	4 channel
Video Output	1 x HDMI , 1 x VGA
Recording Resolution	Configurable from 8.0MP (3840 x 2160) to CIF (352 x 288)
Incoming Bandwidth	80Mbps
Video Compression	H.265 / H.264
Bit Rate	16 ~ 20Mbps per channel
Ethernet	1 x RJ-45 port (10/100Mbps)
PoE	4 ports (IEEE802.3at/af)
Remote View	iOS (iPhone, iPad) / Android devices / Windows Phone* (limited functionality)
Internal HDD	1 x SATA port up to 10TB max, 10TB HDD Capacity

Camera Model		VSIPE2MPVDMINIIRCB3.6
Product Image		
Image Sensor		1/2.8" 2.0MP Progressive Scan CMOS
Lens		3.6mm F2.0 Fixed Lens
Min. Illumination		0.009 Lux/F2.0 (Color), 0 Lux/F2.0 (IR on)
Infrared Range		50m
Lighting Compensation		BLC / HLC / WDR (120dB)
Resolution		1080p (1920 x 1080) to CIF (352 x 288)
Frame Rate	Main	1080p (1~50fps)
	Sub	D1 (1 ~ 50fps)
	Third	1080p (1 ~ 25fps)
Audio Input		Built-in Microphone
Smart Functions		Tripwire, Intrusion, Object Abandoned/Missing, Face Detection, Motion Detection (4 zones), Region of Interest (4 zones), Privacy Masking (4 zones), Smart Infrared
Weather/Vandal Resist		IP67
Power Input		12VDC / PoE (802.3af)

Your local Watchguard[™] IP surveillance professional: