



# 1080p plus audio & infrared.

**Mobile Series: Full HD 1080p HDCVI mobile surveillance cameras in 2.0MP**

Keep every angle of your vehicle covered with Mobile Series surveillance cameras from Securview. Choose from vandal dome, compact dome & bumper cameras, capable of Full HD streaming in durable IP67 rated housings.

- Stream 2.0MP / Full HD 1080p (1920 x 1080) 25fps
- Fixed lens, available in 111° to 83° viewing angles
- Smart infrared illumination, up to 20m range
- Built-in microphone mobile series models available
- IP67 weather resistant metal housings (all models)
- Shock resistant housings with aviation connectors
- DIRFT dome: Low profile & IK10 vandal resistant
- DIRAT dome: Smaller than a tennis ball Ø62 x 62mm
- CIRAT camera: Ideal for bumper placement
- BT camera: Ideal for flush mount in-bumper



**Built-in Mic Models Available**



**20m Infrared and low light vision**



**IP67 Rated Across the Range**

Model	VSCVI2MPVDIRFTV2	VSCVI2MPVDIRFTV3	VSCVI2MPDIRAT	VSCVI2MPCIRAT	VSCVI2MPBT2.8	
General						
	Mobile Wedge Dome		Mobile Dome Camera	Mobile Bumper Camera	Mobile Bullet Camera	
	1/2.8" 2.1 Megapixel CMOS		1/2.9" 2.0 Megapixel CMOS			
	1920(H)x1080(V)		1920 (H) x 1080 (V)			
	Signal Noise Ratio > 65dB					
Camera	2.8mm F1.6 Fixed Lens		3.6mm F1.6 Fixed Lens		2.8mm F2.0 Fixed Lens	
	111°		110°		109°	
	Fixed		Fixed / 0.8m Min. Focus Distance		Fixed / 0.5m Min. Focus Distance	
	0.005 Lux F1.6 (Colour) / 0 Lux IR Active		0.005 Lux at F1.6 (Colour) / 0 Lux IR Active		0.02 Lux F2.0 (Colour) / 0.002 Lux (B/W)	
	1/4 ~ 1/100,000s		1/25 ~ 1/100,000s			
	Auto (ICR) / Manual					
	20m		20m		N/A	
	Auto / Manual					
	2D / 3D		2D			
	Auto					
	BLC / HLC / WDR (120dB)		BLC / HLC / DWDR			
	Video	1080p (1920 x 1080) to CIF (352 x 288)				
25fps (1080p and lower)						
3m / 6m / 12m / 18m heavy duty cables available						
DORI	Detect	39m	55m	57m	40m	
	Observe	15m	22m	23m	16m	
	Recognise	8m	11m	11m	8m	
	Identify	4m	6m	9m	4m	
	N/A					
Interface	N/A					
	1x BNC HDCVI output					
	Support					
	IP67					
Environmental	IK10		N/A			
	Metal, Polycarbonate		Metal			
	12VDC					
	<2.4W		<3.6W		<2.9W	
	Ø106 x 50mm		Ø106 x 50mm		Ø30 x 68mm	
	0.31kg		0.31kg		0.07kg	
	-40° to 60°C / RH90% (max)					
Accessories						