



# Built for road performance.

**Mobile Series: Full HD 1080p HDCVI mobile surveillance cameras in 2.0MP**

Keep every angle of your vehicle covered with Mobile Series surveillance cameras from Securview. Choose from vandal dome, compact dome & bumper cameras, capable of Full HD streaming in durable IP67 rated housings.

- Stream 2.0MP / Full HD 1080p (1920 x 1080) 25fps
- Fixed lens, available in 111° to 83° viewing angles
- Smart infrared illumination, up to 20m range
- Built-in microphone mobile series models available
- IP67 weather resistant metal housings (all models)
- Shock resistant housings with aviation connectors
- DIRFT dome: Low profile & IK10 vandal resistant
- DIRAT dome: Smaller than a tennis ball Ø62 x 62mm
- CIRAT camera: Ideal for bumper placement
- BT camera: Ideal for flush mount in-bumper



**Built-in Mic Models Available**



**20m Infrared and low light vision**



**IP67 Rated Across the Range**

Model	VSCVI2MPVDIRFTV3	VSCVI2MPDIRAT	VSCVI2MPCIRAT	VSCVI2MPBT2.8		
General						
	Product Image					
	Camera Style	Mobile Wedge Dome	Mobile Dome Camera	Mobile Bumper Camera	Mobile Bullet Camera	
	Image Sensor	1/2.8" 2.1 Megapixel CMOS		1/2.9" 2.0 Megapixel CMOS		
	Effective Pixels	1920(H)x1080(V)		1920 (H) x 1080 (V)		
Signal Noise Ratio	> 65dB					
Camera	Lens	2.8mm F1.6 Fixed Lens	3.6mm F2.0 Fixed Lens	3.6mm F2.0 Fixed Lens	2.8mm F2.0 Fixed Lens	
	Angle of View	110°	83°	83°	109°	
	Focus	Fixed	Fixed / 0.8m Min. Focus Distance	Fixed / 0.8m Min. Focus Distance	Fixed / 0.5m Min. Focus Distance	
	Minimum Illumination	0.005 Lux at F1.6 (Colour) / 0 Lux IR Active	0.02 Lux at F2.0 (Colour) / 0 Lux IR Active	0.02 Lux at F2.0 (Colour) / 0 Lux IR Active	0.02 Lux F2.0 (Colour) / 0.002 Lux (B/W)	
	Electronic Shutter	1/4 ~ 1/100,000s		1/25 ~ 1/100,000s		
	Day/Night	Auto (ICR) / Manual				
	Infrared Range	20m	20m	20m	N/A	
	White Balance	Auto / Manual				
	Noise Reduction	2D / 3D	2D			
	Gain Control	Auto				
	Lighting Compensation	BLC / HLC / WDR (120dB)	BLC / HLC / DWDR			
	Video	Resolution	1080p (1920 x 1080) to CIF (352 x 288)			
Frame Rate		25fps (1080p and lower)				
Transmission Distance		3m / 6m / 12m / 18m heavy duty cables available				
DORI	DORI Distance	Detect	39m	57m	57m	40m
		Observe	15m	23m	23m	16m
		Recognise	8m	11m	11m	8m
		Identify	4m	9m	6m	4m
Interface	Audio Input	N/A	Built-in microphone	Built-in microphone	N/A	
	Alarm Interface	N/A				
	Video Output	1x BNC HDCVI output				
	OSD Menu	Support				
Environmental	Ingress Protection	IP67				
	Vandal Resistant	IK10	N/A		N/A	
	Housing	Metal, Polycarbonate	Metal			
	Power Input	12VDC				
	Power Consumption	<3.6W	<2.9W	<2.9W	<0.6W	
	Dimensions	Ø106 x 50mm	Ø62 x 62mm	107 x 43 x 55mm	Ø30 x 68mm	
	Weight	0.31kg	0.16kg	0.31kg	0.07kg	
Operating Environment	-40° to 60°C / RH90% (max)					
Accessories	Product Diagram					

Your local Securview™ HDCVI solutions professional: