

# SECURVIEW™

## 8/16/24/32 Channel Standalone Digital Video Recorder

Models: DVRSVIEW8V4 / 16V4 / 24V4 / 32V4



### Product Overview

The DVRSVIEWV4 series features H.264 video compression, mobile surveillance, multiple backup methods, multiple detection modes, user-friendly GUI and front panel operation as well as a number of other features which make the DVRSVIEW series great value for money. The DVR is ideal for mid to large level surveillance applications.

The DVRSVIEWV4 series is capable of offering mobile surveillance via many popular mobile platforms, supporting popular models such as iPhone & Android (available to download from apps store), Blackberry, Symbian & Window (software available by request).

Specifications		DVRSVIEW8v4	DVRSVIEW16v4	DVRSVIEW24v4	DVRSVIEW32v4
System	Main Processor	Dual-core Embedded Processor			
	Operating System	Embedded Linux			
	Video Input	8 Channel BNC	16 Channel BNC	24 Channel BNC	32 Channel BNC
	Audio Input	8 Channel BNC	16 Channel BNC	24 Channel BNC	32 Channel BNC
	Audio Output	1 Channel BNC			
	Two-way Talk	1 Channel BNC Input / 1 Channel BNC Output			
Display	Video Output	HDMI / VGA / TV / Spot Simultaneous Video Output			
	Resolution	1920 x 1080 / 1280 x 1024 / 1280 x 720 / 1024 x 786			
	Display Split	1/4/8/9	1/4/8/9/16	1/4/8/9/16/25	1/4/8/9/16/25/36
	Privacy Masking	4 Rectangular Zones (Each Camera)			
	OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording			
Recording	Compression	Video: H.264 / Audio: G.711			
	Resolution	4CIF (704 x 576) / CIF (352 x 288)			
	Record Rate	25fps @ D1 (720 x 576) across all channels			
	Bit Rate	48~4096Kb/s			
	Record Modes	Manual, Schedule (Regular/Continuous, MD, Alarm), Stop			
	Record Interval	1~120min (Default: 60min), Pre-record:1~30sec, Post-record:10~300sec			
Detection	Alarm Input	8 Channel	16 Channel		
	Relay Output	5 Channel			
	Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen tips			
	Video Detection	Motion Detection, MD Zones: 396 (22 x 18), Video loss & Camera blank			
Playback & Backup	Sync Playback	1/4/9	1/4/9/16	1/4/9/16/25	1/4/9/16/25/36
	Search Modes	Time/Date, Alarm, MD & Exact search (Accurate to the second), Smart search			
	Backup Modes	USB Device / eSATA Device / Internal SATA Burner / Network			
Network	Ethernet	RJ-45 Port (10/100M/1000M)			
	Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, Alarm Server			
	Max. User Access	20 Users			
	Remote View	iOS, Android & Windows Phone Devices			
Storage	Internal HDD	8 SATA Ports up to 32TB			
Auxiliary	USB Interface	3 Ports	4 Ports		
	RS232	1 Port, for PC Communication & Keyboard			
	RS485	1 Port, for PTZ Control			
General	Power Supply	AC100~240V, 50/60Hz			
	Power Consumption	30W	40W		
	Operating Environment	-10 ~+55°C / 10~90%RH / 86~106kpa			
	Dimensions	440 x 89 x 460mm (W x H x D)			
	Weight	6.5Kg (without HDD)			