

Wireless Mobile Video Monitor Kit

Pair 2 cameras wirelessly in seconds



Boost your driver safety with the Rhino™ Complete 2 Camera Wireless Mobile Monitoring kit. Connect two heavy duty, IP66 cameras wirelessly and stream to a 7" in-car monitor. For additional customisation, you can wire a camera to trigger display on reverse.

Pair cameras wirelessly in seconds with up to 12m wireless range following these three simple steps:

- 1) Connect LCD monitor to 12VDC or 24VDC power;
- 2) Click pair camera to begin auto-discovery;
- 3) Connect power to camera. It is that easy.

Display Specifications	
Display Type	7" Colour TFT LCD
Display Resolution	800 x 480 pixels (SVGA)
AV Modes	NTSC / PAL
PSU Voltage	10 ~ 28VDC
Power	5W
Brightness/Contrast	450cd/m ² / 450:1
Display Split	Single / Dual / Quad
Operating Temperature	-20 ~ 65°C
Trigger Modes	Reverse trigger support

Camera Specifications	
Image Resolution	640 x 480 pixels (VGA)
Minimum Illumination	0.1 Lux
Lens	2.0mm Fixed Focal Length
Infrared LEDs	12pcs
White Balance	Auto
Ingress Protection	IP66
Transmission Frequency	2.4GHz
Input Voltage	7.5VDC 500mA
Operating Conditions	-20 ~ 75°C / 65% Max. RH

Your local Rhino™ Professional: