



Seamless HDCVI upgrades.


Professional Series: 2.0MP HDCVI Synergy DVRs in 4, 8, 16 & 32 channels

Securview Victory Series Professional HDCVI DVRs offer 5 times the image resolution of D1 analogue surveillance in a wide range of sizes. They also support other popular HD over coax technologies, analogue & IP video inputs.

- Records up to 2.0MP/1080p at 15fps (HDCVI, HDTV, AHD) and 960H at 25fps (analogue)
- Add additional IP channels up to 5.0MP resolution
- High capacity storage, up to 80TB (32ch model)
- HDMI & VGA simultaneous video output
- Backup via external USB device or local network
- Configure remote view in seconds via QR code
- Remote view for iOS, Android & Windows Phone



5x Greater Resolution vs D1



Victory Synergy Compatibility



Remote View via QR Code

Model	CVR4V6	CVR8V6	CVR16V6	CVR32V3
Product Image				
Main Processor	Embedded Processor			
Operating System	Embedded Linux OS			
Video Input	4 channel BNC	8 channel BNC	16 channel BNC	32 channel, BNC
Camera Configurations	Coaxial: 4 channels up to 1080p/15fps (HDCVI, HDTV, AHD), 960H/25fps (analogue) Network: Add 2 channels up to 5.0MP Max 24Mbps Incoming Bandwidth	Coaxial: 8 channels up to 1080p/15fps (HDCVI, HDTV, AHD), 960H/25fps (analogue) Network: Add 4 channels up to 5.0MP Max 48Mbps Incoming Bandwidth	Coaxial: 16 channels up to 1080p/15fps (HDCVI, HDTV, AHD), 960H/25fps (analogue) Network: Add 8 channels up to 5.0MP Max 96Mbps Incoming Bandwidth	Coaxial: 32 channels up to 1080p/15fps (HDCVI, HDTV, AHD), 960H/25fps (analogue) Network: Add 32 channels up to 5.0MP Max 128Mbps Incoming Bandwidth
Audio In/Out	4 / 1			16 / 1
Two-way Talk	Reuse channel 1 audio input / output RCA			1 channel input / output BNC
Video Output	1 HDMI / 1 VGA			2 HDMI / 1 VGA / 1 TV (BNC)
Display Resolution	1920 x 1080 / 1280 x 1024 / 1280 x 720 / 1024 x 768			
Display Split	1 / 4 / 6	1 / 4 / 8 / 9 / 16	1 / 4 / 8 / 9 / 16 / 25	1 / 4 / 8 / 9 / 16 / 25 / 36
OSD	Camera title, time, video loss, camera lock, MD & recording			
Maximum Resolution	1080p (1920 x 1080) / 720p (1280 x 720)			
Frame Rate	Main: 1080p (1~15fps), 720p (1~25fps) Sub: D1 (1~25fps)			
Video Compression	H.264+ / H.264			
Bit Rate	1~6144Kbps per channel			
Record Modes	Manual / Schedule (Regular, Continuous), Motion Detection, Alarm, Stop			
Record Interval	1~60 min (default: 60 min) / Pre: 1~30s / Post: 10~300s			
Alarm Input / Output	8 channel input / 3 relay output		16 channel input / 3 relay output	
Trigger Events	Recording; PTZ; tour; alarm; push video notification; email notification; FTP upload; snapshot; internal buzzer; and screen tip overlay			
Video Detection	MD zones: 396 (22 x 18) / Video loss / Camera blank			
Playback Sync	1 / 4	1 / 4 / 9	1 / 4 / 9 / 16	1 / 4 / 9 / 16
Search Modes	Time/Date; Alarm; Motion detection; Exact search (to the second); Smart Search			
Intelligent Functions	Face Detection			
Backup Modes	USB Device / Internal SATA burner / Network			USB Device / eSATA Device / Internal SATA burner (optional) / Network
Ethernet	1x RJ-45 port (10/100M)		1x RJ-45 port (10/100M/1000M)	
Network Functions	HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search			
Max. User Access	128 users			
Remote View	iOS (iPhone, iPad), Android devices, Windows Phone			
Internal HDD	1 SATA port, up to 6TB total	2 SATA ports, up to 20TB total		8 SATA Ports, up to 80TB total
USB Interface	2 ports: USB2.0		2 ports: 1x USB2.0, 1x USB3.0	
Auxiliary Inputs	1 x RS485 port (for PTZ)			1 x RS232 port (PC comm. & keyboard) / 1 x RS485 (PTZ control)
Power Supply	12VDC/2A	12VDC/4A	12VDC/5A	
Power Consumption	<10W (without HDD)	<15W (without HDD)		<35W (without HDD)
Operating Environment	-10 ~55°C / 10~90%RH / 86~106kpa			
Dimensions	325mm x 255mm x 55mm (1U)	375mm x 285mm x 55mm (1U)		440mm x 455mm x 95mm (2U)
Weight	1.5kg (without HDD)	2.35kg (without HDD)		6.5kg (without HDD)
Product Diagram				

Your local Securview™ HDCVI solutions professional: