



The complete package.

HD Network Surveillance Kits: Available with 4, 8 or 16 cameras

The VIP Vision high definition propacks are a complete network surveillance system, built for rapid installation and impressive results. They are an ideal CCTV package for business and residential applications.

- Records 2.0MP (1920 x 1080) at 25fps real-time
- 2.0MP True WDR 50m IR IP67 dome cameras
- 2.0MP True WDR 40m IR IP67 bullet cameras
- Remote view in seconds with setup via QR code
- HDMI & VGA simultaneous video output
- Built-in Power over Ethernet (PoE)
- Pre-installed surveillance grade hard disk drive
- Remote view for iOS, Android & Windows Phone





IP67 Weather Resistant





Remote View Capabilities



Includes Cabling and HDD

CCTV KIT		NVR4PROPACK3	NVR8PROPACK6	NVR16PROPACK6
Product Image				
NVR Model		NVR4PRO3	NVR8PRO6	NVR16PRO6
Main Processor		Quad-core embedded processor		
Operating System		Embedded Linux		
Video Input		4 channel	8 channel	16 channel
Two-way Talk		1 channel input / 1 channel output / RCA		
ONVIF Conformance		2.4 Conformance		
Video Output		1x HDMI / 1x VGA	1x HDMI / 1x VGA	2 x HDMI / 1x VGA
Display Resolution		Configurable from 1920 x 1080 to 1024 x 768	Configurable from 3840 x 2160 to 1024 x 768	
Display Split		1/4	1/4/8/9	1/4/8/9/16
OSD		Camera title, Time, Video loss, Camera lock, Motion detection, Recording		
Maximum Resolution		Configurable from 8.0MP(3840 x 2160) to CIF (352 x 288)	Configurable from 12.0MP(4000 x 3000) to CIF (352 x 288)	
Incoming Bandwidth		200Mbps	320Mbps	
Video Compression		H.265 / H.264	H.265 / H.264 / MJPEG / MPEG4	
Bit Rate		16 ~ 20Mbps per channel		
Alarm Input / Output		4 channels input / 2 channels relay output	4 channels input / 2 channels relay output	16 channels input / 6 channels relay output
Trigger Events		Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Snapshot, Buzzer, Screentips		
Video Detection		Motion Detection, Motion Zones: 396 (22 x 18), Video Loss & Tampering		
Playback Sync		1/4	1/4/9	1/4/9/16
Search Modes		Time/Date, Alarm, By Motion, Exact search, Smart search		
Backup Modes		USB Device / Network	USB Device / Network	USB Device / Network / eSATA Device / Internal SATA burner
Ethernet		1 RJ-45 port (10/100/1000Mbps)		
Power over Ethernet		4 ports (IEEE802.3at/af)	8 ports (IEEE802.3at/af)	16 ports (IEEE802.3at/af)
Max. User Access		128 users		
Remote View		iOS (iPhone, iPad) / Android devices / Windows Phone		
Internal HDD		2 SATA ports, up to 12TB (1TB pre-installed)	2 SATA ports, up to 12TB (2TB pre-installed)	4 SATA ports, up to 24TB (4TB pre-installed)
USB Interface		2 ports: Rear USB3.0 / Front USB2.0	2 ports: Rear USB3.0 / Front USB2.0	3 ports: Rear USB3.0 / Front USB2.0
Auxiliary Inputs		N/A	1 x RS232 / 1 x RS485	1 x RS232 / 1 x RS485 / 1 x eSATA
Power Supply		48VDC 2A	100 ~ 240VAC, 50 ~ 60Hz	100 ~ 240VAC, 50 ~ 60Hz
Operating Environment		-10 ~ 55°C / 10 ~ 90%RH / 86 ~ 106kpa	-10 ~ 55°C / 10 ~ 90%RH / 86 ~ 106kpa	-10 ~ 55°C / 10 ~ 90%RH / 86 ~ 106kpa
Dimensions		375 x 282 x 56mm	375 x 328 x 53mm	440 x 411 x 76mm
Weight		1.60kg (without HDD)	2.60kg (without HDD)	4.65kg (without HDD)

Camera Model		VSIP2MPVDMINIIRC3.6	VSIP2MPFBMINIIRV2
Product Image			
Camera Style		Mini Dome	Mini Bullet
Image Sensor		1/2.7" 2.0 Megapixel Progressive Scan CMOS	
Lens		3.6mm F2.0 Fixed Lens	3.6mm F2.2 Fixed Lens
Day/Night		Auto (ICR) / Colour / B&W	
Infrared Range		50m	40m
Lighting Compensation		BLC / HLC / WDR (120dB)	
Resolution		Configurable from 2.0MP (1920 x 1080) to CIF (352 x 288)	
Frame Rate		1080p and lower (1 ~ 25fps)	
		D1 and lower (1 ~ 25fps)	
		720p and lower (1~13fps)	
Audio Input		Built-in Microphone	N/A
Smart Functions		Tripwire / Intrusion / Abandoned & Missing Object Detection / Scene Change / Audio Detection / Face Detection	
Ingress Protection		IP67	
Vandal Resistant		N/A	
Power Input		12VDC / PoE (802.3af)	

Your local VIP Vision™ professional: