



The complete package.

4.0MP Network Surveillance Kits: Available with 4, 8 or 16 cameras

The VIP Vision 4.0MP propack series is a complete network surveillance system, built for rapid installation and impressive results. It is an ideal CCTV package where high resolution and usable evidence is paramount.

- Records 4.0MP (2688 x 1520) at 25fps real-time
- 4.0MP True WDR 50m IR IP67 dome cameras
- 4.0MP True WDR 40m IR IP67 bullet cameras
- Remote view in seconds with setup via QR code
- HDMI & VGA simultaneous video output
- Built-in Power over Ethernet (PoE)
- Pre-installed surveillance grade hard disk drive
- Remote view for iOS, Android & Windows Phone



IP67 Weather Resistant



Remote View Capabilities



Includes Cabling and HDD

Choose from three comprehensive, ready to install packages.

The VIP Vision 4.0MP propack series offers complete 4, 8 and 16 channel network surveillance packages, purpose built for capturing high resolution video and usable evidence.



4 Channel <small>NVR4PROPACK2-4M</small>	4 Channel Professional NVR <ul style="list-style-type: none"> 4 port Power over Ethernet switch Records 4.0MP at 25fps Pre-installed 2TB hard disk drive (additional backup via USB device or network) 	4x 4.0MP Infrared Cameras <ul style="list-style-type: none"> 2x bullet and 2x dome cameras 3.6mm (87°) fixed lens with True WDR Stream up to 4.0MP (2688 x 1540) IP67 rated metal housing for outdoor use 	All required cabling <ul style="list-style-type: none"> CAT5 cabling for cameras: 2 x 10m, 1 x 20m, 1 x 30m CAT5 patch cable for networking: 1 x 1.5m HDMI output cable: 1 x 1m 1 x NVR Remote and 1 x Mouse 	
	8 Channel <small>NVR8PROPACK6-4M</small>	8 Channel Professional NVR <ul style="list-style-type: none"> 8 port Power over Ethernet switch Records 4.0MP at 25fps Pre-installed 4TB hard disk drive (additional backup via USB device or network) 	8x 4.0MP Infrared Cameras <ul style="list-style-type: none"> 4x bullet and 4x dome cameras 3.6mm (87°) fixed lens with True WDR Stream up to 4.0MP (2688 x 1540) IP67 rated metal housing for outdoor use 	All required cabling <ul style="list-style-type: none"> CAT5 cabling for cameras: 4 x 10m, 2 x 20m, 2 x 30m CAT5 patch cable for networking: 1 x 1.5m HDMI output cable: 1 x 1m 1 x NVR Remote and 1 x Mouse
	16 Channel <small>NVR16PROPACK6-4M</small>	16 Channel Professional NVR <ul style="list-style-type: none"> 16 port Power over Ethernet switch Records 4.0MP at 25fps Pre-installed 8TB hard disk drive (additional backup via USB device or network) 	16x 4.0MP Infrared Cameras <ul style="list-style-type: none"> 8x bullet and 8x dome cameras 3.6mm (87°) fixed lens with True WDR Stream up to 4.0MP (2688 x 1540) IP67 rated metal housing for outdoor use 	All required cabling <ul style="list-style-type: none"> CAT5 cabling for cameras: 8 x 10m, 4 x 20m, 4 x 30m CAT5 patch cable for networking: 1 x 1.5m HDMI output cable: 1 x 1m 1 x NVR Remote and 1 x Mouse

Technical Specifications.

For full specifications and bracket compatibility, please see the individual unit web entry or datasheet.

NVR Model	NVR4PRO3	NVR8PRO6	NVR16PRO6
Product Image			
Video Input	4 channel	8 channel	16 channel
Two-way Talk	1 channel input / 1 channel output / RCA		
Video Output	1x HDMI / 1x VGA	1x HDMI / 1x VGA	2 x HDMI / 1x VGA
Maximum Resolution	Configurable from 8.0MP (3840 x 2160) to CIF		
Incoming Bandwidth	200Mbps	320Mbps	
Video Compression	H.265 / H.264	H.265 / H.264 / MJPEG / MPEG4	
Bit Rate	16 ~ 20Mbps per channel		
Alarm Input / Output	4 channels input / 2 channels relay output	4 channels input / 2 channels relay output	16 channels input / 6 channels relay output
Internal HDD	2 SATA ports, up to 12TB (2TB pre-installed)	2 SATA ports, up to 12TB (4TB pre-installed)	4 SATA ports, up to 24TB (8TB pre-installed)
Power Supply	48VDC 2A	100 ~ 240VAC, 50 ~ 60Hz	100 ~ 240VAC, 50 ~ 60Hz

Camera Model	VSIP4MPVDMINIIRC3.6	VSIP4MPFBMINIIR	
Product Image			
Image Sensor	1/3" 4.0MP Progressive Scan CMOS		
Infrared Range	50m	40m	
Lighting Compensation	BLC / HLC / WDR (120dB)		
Resolution	4.0MP (2688 x 1520) to CIF(352 x 288)		
Frame Rate	Main	4.0MP (1~25fps)	4.0MP (1~20fps)
	Sub	D1 (1 ~ 25fps)	D1 (1 ~ 25fps)
	Third	720p (1 ~ 25fps)	720p (1 ~ 5fps)
Audio Input	Built-in Microphone	N/A	
Smart Functions	Face Detection, Motion Detection (4 zones), Region of Interest (4 zones), Privacy Masking (4 zones), Smart Infrared		
Power Input	12VDC / PoE (802.3af) (Class 0)		