



## Reliable backup power.

Uninterruptible Power Supply Series: Available in 600VA, 1500VA & On-Line 1000VA

Provide short-term battery power for your security systems during power outages with the Securview Uninterruptible Power Supply range. The wide input/output voltage range of the series makes them suitable for use with many devices.

- Wide input and output voltage range
- Economy mode for better energy efficiency
- Provide power backup for up to four 3 Pin Plugs
- Prevent hardware damage from sudden power spikes
- Overload, overcharge and ESD protection
- Alarm alerts for battery mode, faults and low power
- On-line UPS for instant power transfer (*B1000 only*)
- Comprehensive LCD display shows load level, battery level, current mode and fault indicators (*B1000 only*)
- Network functionality via USB/RS-232 port (*B1000 only*)



Electronic Surge Protection



Alarm Siren when Issue Detected



Versatile Functionality

# Series Specifications

Model	UPS-A600-L	UPS-A1500-L	UPS-B1000-O	
General				
				
				
	Capacity	600VA / 360W	1500VA / 900W	1000VA / 900W
Operation	Line Interactive		Smart On-Line	
Protection	Overload, Overcharge, ESD			
Input	110VAC ~ 120VAC / 220VAC ~ 240VAC			
	Input Voltage	110VAC ~ 120VAC / 220VAC ~ 240VAC		
	Voltage Range	81 ~ 145VAC / 162 ~ 290VAC	81 ~ 145VAC / 162 ~ 290VAC	55VAC ~ 145VAC / 110VAC ~ 300VAC
	Frequency Range	40Hz ~ 70Hz		
Power Factor	0.9			
Output	100 / 110 / 115 / 120 / 200 / 208 / 220 / 230 / 240VAC			
	Output Voltage	100 / 110 / 115 / 120 / 200 / 208 / 220 / 230 / 240VAC		
	AC Voltage Regulation (Battery Mode)	±10%	±10%	±1%
	Frequency Range (Battery Mode)	50Hz / 60Hz ±0.5%		
	Transfer Time	2-6ms	2-6ms	0ms
Waveform (Batt. Mode)	Simulated Sinewave			
Battery	Battery Type	1 X 12v/7Ah	1 X 12v/7Ah	2 x 12V/9Ah
	Recharge Time	4 - 6 hours to 90% capacity (Average)		
	Charging Voltage	27.4V ±1%		
Interface	LCD Screen	N/A	N/A	Load level / Battery level / AC mode / Battery mode / Bypass mode / Fault indicators
	Alarm	Overload - Tone every 0.5 seconds Low battery - Tone every 1 second Battery mode - Tone every 10 seconds Fault - Continuous tone		
Environment	Noise Level	<40dB	<40dB	<50dB
	Operating Environment	0 ~ 40°C / 90%RH		
	Dimensions	279 x 101 x 142mm	320 x 130 x 182mm	282 x 145 x 220mm
	Weight	4.2kg	10.4kg	9.8kg
Accessories				
				
				

Your local Securview™ professional: