

Compact Series 1080p Fixed HDCVI Mini Dome

Model: VSCVI2MPDIRV4





Model	VSCVI2MPDIRV4
General	
Camera Style	Weather Resistant Mini Dome
Image Sensor	1/2.2" 2.0 Megapixel CMOS
Effective Pixels	1930 (H) x 1088 (V)
Signal Noise Ratio	> 50dB
Camera	
Lens	3.6mm Fixed Lens
Angle of View	90°
Electronic Shutter	1/50 ~ 1/100,000s
Minimum Illumination	0.02 Lux at F1.6 (Colour) / 0 Lux IR Active
Day/Night	Auto (ICR) / Colour / B&W
White Balance	Auto
Noise Reduction	2D
Gain Control	Auto
Backlight Compensation	BLC
Audio Input	N/A
Transmission Distance	Over 500m via 75-3 coaxial cable
Synchronisation	Internal
OSD Menu	Support
Alarm Interface	N/A
Video	
Video Compression	H.264
Resolution	1080p (1920 x 1080) to CIF (352 x 288)
Frame Rate	25fps (1080p and lower)
Video Output	1 x BNC SD/HD video output (switchable)
Environment	
Ingress Protection	IP67
Vandal Resistant	No
Maximum Infrared Range	50m
Power Input	12VDC
Power Consumption	< 4.5W
Dimensions	Ø106 x 94mm
Weight	0.45kg
Operating Environment	-30° to 60°C / RH95% (max)
Product Diagram	

Quadruple your image resolution with the Watchguard range of compact HDCVI cameras. Stream in real-time at 1080p Full HD with this weather resistant, full metal housing surveillance camera.

Camera Features

- Streams HD 1080p/2.0MP (1920 x 1080)
- Fixed 3.6mm lens; 90° viewing angle
- Up to 500m HD video transmission over coax
- Infrared illumination up to 50m
- IP67 rated for weather resistance
- Compact size with adjustable mount
- Full metal housing



Compatible Accessories

Accessories sold separately, additional adapters may be required.



VSBKTA139



VSBKTB204W



VSBKTA150



VSBKTA151



VSBKTA152

Your local Watchguard™ professional: