



Crystal clear images over coax.

Professional Series: Motorised lens HDCVI domes available in 2.0MP & 4.0MP

With a flat lens window and up to 4.0MP resolution, the E-range from the Securview Professional Series offers crystal clear images with no distortion, day or night. It also features dual power & HD/SD outputs, for easy installation.

- Stream up to 4.0MP (2560 x 1440) at 25fps
- Motorised varifocal 2.7 ~ 12mm lens with fixed iris
- Up to 700m video transmission over coaxial cable
- Smart infrared illumination, up to 60m range
- Dual BNC outputs for HD and composite video
- True WDR (120dB) and 2D/3D noise reduction
- Dual voltage compatible: 12VDC and 24VAC
- IP67 rated weather resistant metal housing



Up to 9x Image Resolution vs D1



Long Range Infrared



Weather Resistant Housing



Model	VSCVI2MPVDIRME	VSCVI4MPVDIRME				
Image Sensor	1/2.7" 2.1 Megapixel CMOS	1/3" 4.1 Megapixel CMOS				
Effective Pixels	1928 (H) x 1088 (V)	2688 (H) x 1520 (V)				
Signal Noise Ratio	> 65dB					
Lens	2.7 ~ 12mm F1.4 Motorised Lens; Fixed Iris	2.7 ~ 12mm F1.3 Motorised Lens; Fixed Iris				
Angle of View	99° (wide) ~ 37° (tele)	98° (wide) ~ 26° (tele)				
Focus	Auto/Manual / 0.3m Min. Focus Distance	Auto/Manual / 0.2m Min. Focus Distance				
Minimum Illumination	0.03 Lux at F1.4 (Colour) / 0 Lux IR Active	0.01 Lux at F1.3 (Colour) / 0 Lux IR Active				
Electronic Shutter	1/3 ~ 1/300,000s	1/4 ~ 1/100,000s				
Day/Night	Auto (ICR) / Manual					
Infrared Range	60m					
White Balance	Auto / Manual					
Noise Reduction	2D / 3D					
Gain Control	Auto					
Lighting Compensation	BLC / HLC / WDR (120dB)					
Resolution	1080p (1920 x 1080) to CIF (352 x 288)	4.0MP (2560 x 1440) to CIF (352 x 288)				
Frame Rate	25fps (1080p and lower)	25fps (4.0MP), 25fps (1080p and lower)				
Transmission Distance	Rated for up to 700m via 75-3 coaxial cable (performed in ideal test conditions)					
Audio Input	N/A					
Alarm Interface	N/A					
Video Output	2 x BNC video output (1 x HDCVI / 1 x Composite SD)					
Synchronisation	Internal					
OSD Menu	Support					
Ingress Protection	IP67					
Vandal Resistant	N/A					
Housing	Metal					
Power Input	12VDC / 24VAC					
Power Consumption	< 12.0W					
Dimensions	Ø122 x 105mm					
Weight	0.58kg	0.62kg				
Operating Environment	-30° to 60°C / RH95% (max)					
Diagram						
Accessories						
Models	Junction Box (VSBKTA137)	Wall Mount (VSBKTB203W)	Wall Mount Rain Shield (VSBKTA200W)	Ceiling Extension (VSBKTA106 + VSBKTB220C)	Right Angle Wall Mount (VSBKTA106 + VSBKTB305W)	Pole Mount (VSBKTB203W + VSBKTA152)

Your local Securview™ HDCVI solutions professional: