



HD surveillance made easy.

Professional Series: 2.0MP IP surveillance kits available in 4, 8 and 16 channels

The VIP Vision Full HD propack series of complete network surveillance systems are built for rapid installation and impressive results. They are ideal CCTV solutions for business, commercial and residential applications.

- Records 2.0MP (1920 x 1080) at 25fps real-time
- 2.0MP True WDR 50m IR fixed lens dome cameras
- 2.0MP True WDR 40m IR fixed lens bullet cameras
- Pre-installed HDD and all necessary cabling included
- IP67 weather resistant cameras for external use
- Native Ultra HD live view on 4K monitors via HDMI
- HDMI & VGA simultaneous video output
- Built-in Power over Ethernet (PoE) for easy installation
- Up to 320Mbps incoming bandwidth; H.265 support
- Remote view for iOS, Android & Windows Phone



Ready-to-Install with Cabling and HDD



Built-in Power over Ethernet



Comprehensive Remote View

Model	NVR4PROPACK3HD	NVR8PROPACK6HD	NVR16PROPACK6HD	
General				
	Recorder	4 Channel NVR with PoE (NVR4PRO3)	8 Channel NVR with PoE (NVR8PRO6)	16 Channel NVR with PoE (NVR16PRO6)
	Included Cameras (Specifications below)	2 x 2.0MP Mini Dome (VSIPE2MPVDMINIIRCB3.6) 2 x 2.0MP Mini Bullet (VSIIP2MPFBMINIIRV3)	4 x 2.0MP Mini Dome (VSIPE2MPVDMINIIRCB3.6) 4 x 2.0MP Mini Bullet (VSIIP2MPFBMINIIRV3)	4 x 2.0MP Mini Dome (VSIPE2MPVDMINIIRCB3.6) 4 x 2.0MP Mini Bullet (VSIIP2MPFBMINIIRV3)
Display	Installed HDD Size	1TB	2TB	4TB
	Video Output	1 x HDMI, 1 x VGA	1 x HDMI, 1 x VGA	2 x HDMI, 1 x VGA
	Display Resolution	Configurable from 3840 x 2160 to 1024 x 768		
Recording	Display Split	1/4	1/4/8/9	1/4/8/9/16
	Recording Resolution	Configurable from 8.0MP (3840 x 2160) to CIF (352 x 288)	Configurable from 12.0MP (4000 x 3000) to CIF (352 x 288)	
	Incoming Bandwidth	200Mbps	320Mbps	
	Video Compression	H.265 / H.264	H.265 / H.264 / MJPEG / MPEG4	
Features	Bit Rate	16kbps ~ 20Mbps per channel		
	Alarm Input / Output	4 channels input / 2 channels relay output (N.O/N.C)		16 channels input / 6 channels relay output (N.O/N.C)
	Playback Sync	1/4	1/4/9	1/4/9/16
Network	Backup Modes	USB Device / Network		USB Device / Network / eSATA Device / Internal SATA burner
	Ethernet	1 x RJ-45 port (10/100/1000Mbps)		
	Power over Ethernet	4 ports (IEEE802.3at/af)	8 ports (IEEE802.3at/af)	16 ports (IEEE802.3at/af)
Storage	Network Functions	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search, P2P		
	Remote View	iOS (iPhone, iPad) / Android devices / Windows Phone* (limited functionality)		
	Internal HDD	2 x SATA ports, up to 20TB		4 x SATA ports, up to 40TB
	HDD Modes	Single (no RAID compatibility)		
Environment	USB Interface	2 ports: Rear USB3.0 / Front USB2.0		3 ports: Rear USB3.0 / Front USB2.0
	Auxiliary Inputs	N/A	1 x RS232 / 1 x RS485	1 x RS232 / 1 x RS485 / 1 x eSATA
	Power Supply	48VDC / 2A	100 ~ 240VAC, 50 ~ 60Hz	
	Power Consumption	< 9W (without HDD)	< 14.5W (without HDD)	< 17.5W (without HDD)
Application	Operating Environment	-10 ~ 55°C / 10 ~ 90%RH / 86 ~ 106kpa		
	Dimensions / Rack Units	375 x 282 x 56mm / 1U	375 x 328 x 53mm / 1U	440 x 411 x 76mm / 1.5U
	Weight	1.60kg (without HDD)	2.60kg (without HDD)	4.65kg (without HDD)
Camera	Included Cabling			
		CAT5 cabling: 2 x 10m, 1 x 20m, 1 x 30m CAT5 patch cable for networking: 1 x 1.5m 1 x HDMI cable for high definition video output 1 x NVR Remote 1 x Mouse	CAT5 cabling: 4 x 10m, 2 x 20m, 2 x 30m CAT5 patch cable for networking: 1 x 1.5m 1 x HDMI cable for high definition video output 1 x NVR Remote 1 x Mouse	CAT5 cabling: 8 x 10m, 4 x 20m, 4 x 30m CAT5 patch cable for networking: 1 x 1.5m 1 x HDMI cable for high definition video output 1 x NVR Remote 1 x Mouse
	Camera	2.0MP Mini Dome (VSIPE2MPVDMINIIRCB3.6)		2.0MP Mini Bullet (VSIIP2MPFBMINIIRV3)
Image Sensor	1/3" 2.0MP Progressive Scan CMOS			
Lens	3.6mm F2.0 Fixed Lens, Horizontal: 87°, Vertical: 48°			
Infrared Range	50m	40m		
Lighting Compensation	BLC / HLC / WDR (120dB)			
Resolution	2.0MP (1920 x 1080) to CIF(352 x 288)			
Frame Rate	Main	1080p (1~50fps)		
	Sub	D1 (1 ~ 50fps)		
	Third	1080p (1 ~ 25fps)		
Audio Input	Built-in Microphone		N/A	
Smart Functions	Face Detection, Motion Detection (4 zones), Region of Interest (4 zones), Privacy Masking (4 zones), Smart Infrared			
Power Input	12VDC / PoE (802.3af)			

Your local VIP Vision™ IP solutions professional: