



# The complete package.

Professional Series: 4.0MP IP surveillance kits available in 4, 8 and 16 channels

The VIP Vision 4.0MP propack series of complete network surveillance systems are built for rapid installation and impressive results. They are ideal CCTV solutions for when high resolution and usable evidence are paramount.

- Records 4.0MP (2688 x 1520) at 25fps real-time
- 4.0MP True WDR 50m IR fixed lens dome cameras
- 4.0MP True WDR 40m IR fixed lens bullet cameras
- Pre-installed HDD and all necessary cabling included
- IP67 weather resistant cameras for external use
- Native Ultra HD live view on 4K monitors via HDMI
- HDMI & VGA simultaneous video output
- Built-in Power over Ethernet (PoE) for easy installation
- Up to 320Mbps incoming bandwidth; H.265 support
- Remote view for iOS, Android & Windows Phone



Ready-to-Install with Cabling and HDD



Built-in Power over Ethernet



Comprehensive Remote View

Model	NVR4PROPACK3-4M	NVR8PROPACK6-4M	NVR16PROPACK6-4M		
General					
Recorder	4 Channel NVR with PoE (NVR4PRO3)	8 Channel NVR with PoE (NVR8PRO6)	16 Channel NVR with PoE (NVR16PRO6)		
Included Cameras (Specifications below)	2 x 4.0MP Mini Dome (VSIP4MPVDMINIIRCB3.6) 2 x 4.0MP Mini Bullet (VSIP4MPFBMINIIR)	4 x 4.0MP Mini Dome (VSIP4MPVDMINIIRCB3.6) 4 x 4.0MP Mini Bullet (VSIP4MPFBMINIIR)	4 x 4.0MP Mini Dome (VSIP4MPVDMINIIRCB3.6) 4 x 4.0MP Mini Bullet (VSIP4MPFBMINIIR)		
Installed HDD Size	2TB	4TB	8TB		
Display	Video Output	1 x HDMI, 1 x VGA	1 x HDMI, 1 x VGA	2 x HDMI, 1 x VGA	
	Display Resolution	Configurable from 3840 x 2160 to 1024 x 768			
	Display Split	1/4	1/4/8/9	1/4/8/9/16	
Recording	Recording Resolution	Configurable from 8.0MP (3840 x 2160) to CIF (352 x 288)	Configurable from 12.0MP (4000 x 3000) to CIF (352 x 288)		
	Incoming Bandwidth	200Mbps	320Mbps		
	Video Compression	H.265 / H.264	H.265 / H.264 / MJPEG / MPEG4		
	Bit Rate	16kbps ~ 20Mbps per channel			
Features	Alarm Input / Output	4 channels input / 2 channels relay output (N.O/N.C)		16 channels input / 6 channels relay output (N.O/N.C)	
	Playback Sync	1/4	1/4/9	1/4/9/16	
	Backup Modes	USB Device / Network		USB Device / Network / eSATA Device / Internal SATA burner	
Network	Ethernet	1 x RJ-45 port (10/100/1000Mbps)			
	Power over Ethernet	4 ports (IEEE802.3at/af)	8 ports (IEEE802.3at/af)	16 ports (IEEE802.3at/af)	
	Network Functions	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search, P2P			
Storage	Remote View	iOS (iPhone, iPad) / Android devices / Windows Phone* (limited functionality)			
	Internal HDD	2 x SATA ports, up to 20TB		4 x SATA ports, up to 40TB	
	HDD Modes	Single (no RAID compatibility)			
	USB Interface	2 ports: Rear USB3.0 / Front USB2.0		3 ports: Rear USB3.0 / Front USB2.0	
Environment	Auxiliary Inputs	N/A	1 x RS232 / 1 x RS485	1 x RS232 / 1 x RS485 / 1 x eSATA	
	Power Supply	48VDC / 2A	100 ~ 240VAC, 50 ~ 60Hz		
	Power Consumption	< 9W (without HDD)	< 14.5W (without HDD)	< 17.5W (without HDD)	
	Operating Environment	-10 ~ 55°C / 10 ~ 90%RH / 86 ~ 106kpa			
	Dimensions / Rack Units	375 x 282 x 56mm / 1U	375 x 328 x 53mm / 1U	440 x 411 x 76mm / 1.5U	
Weight	1.60kg (without HDD)	2.60kg (without HDD)	4.65kg (without HDD)		
Application					
	Included Cabling	CAT5 cabling: 2 x 10m, 1 x 20m, 1 x 30m CAT5 patch cable for networking: 1 x 1.5m 1 x HDMI cable for high definition video output 1 x NVR Remote 1 x Mouse	CAT5 cabling: 4 x 10m, 2 x 20m, 2 x 30m CAT5 patch cable for networking: 1 x 1.5m 1 x HDMI cable for high definition video output 1 x NVR Remote 1 x Mouse	CAT5 cabling: 8 x 10m, 4 x 20m, 4 x 30m CAT5 patch cable for networking: 1 x 1.5m 1 x HDMI cable for high definition video output 1 x NVR Remote 1 x Mouse	
Camera	Camera	4.0MP Mini Dome (VSIP4MPVDMINIIRCB3.6)		4.0MP Mini Bullet (VSIP4MPFBMINIIR)	
	Image Sensor	1/3" 4.0MP Progressive Scan CMOS			
	Lens	3.6mm F2.0 Fixed Lens, Horizontal: 87°, Vertical: 48°		3.6mm F2.1 Fixed Lens, Horizontal: 84°, Vertical: 56°	
	Infrared Range	50m		40m	
	Lighting Compensation	BLC / HLC / WDR (120dB)			
	Resolution	4.0MP (2560 x 1440) to CIF (352 x 288)			
	Frame Rate	Main	4.0MP (1 ~ 25fps)		4.0MP (1~20fps) / 3.0MP (1~25fps)
		Sub	D1 (1 ~ 25fps)		720p (1~5fps WDR on) / (1~18fps WDR off)
		Third	720p (1 ~ 25fps)		1080p (1 ~ 25fps)
	Audio Input	Built-in Microphone		N/A	
Smart Functions	Tripwire, Intrusion, Object Abandoned/Missing, Face Detection, Motion Detection (4 zones), Region of Interest (4 zones), Privacy Masking (4 zones), Smart Infrared		Scene Change / Face Detection		
Power Input	12VDC / PoE (802.3af)				

Your local VIP Vision™ IP solutions professional: