



Instant 4K surveillance.

Professional Series: 8.0MP IP surveillance kits available in 4, 8 and 16 channels

The VIP Vision 8.0MP PROPACK series of complete network surveillance systems are built for rapid installation and impressive results. These kits features everything you need to deliver a complete 4K resolution IP surveillance system.

- Records 8.0MP (3840 x 2160) at 15fps real-time
- 8.0MP 50m IR 4mm fixed lens dome cameras
- 8.0MP 40m IR 4mm fixed lens bullet cameras
- Pre-installed HDD and all necessary cabling included
- IP67 weather resistant cameras for external use
- Native Ultra HD live view on 4K monitors via HDMI
- HDMI & VGA simultaneous video output
- Built-in Power over Ethernet (PoE) for easy installation
- Up to 320Mbps incoming bandwidth; H.265 support
- Remote view for iOS, Android & Windows Phone



Ready-to-Install with Cabling and HDD



Built-in Power over Ethernet



Comprehensive Remote View

Model		NVR4PROPACK3-8M	NVR8PROPACK6-8M	NVR16PROPACK6-8M	
General	Product Image				
	Recorder	4 Channel NVR with PoE (NVR4PRO3)	8 Channel NVR with PoE (NVR8PRO6)	16 Channel NVR with PoE (NVR16PRO6)	
	Included Cameras (Specifications below)	2 x 8.0MP Mini Dome (VSIP8MPVDMINIIRC) 2 x 8.0MP Mini Bullet (VSIP8MPFBMINIIR)	4 x 8.0MP Mini Dome (VSIP8MPVDMINIIRC) 4 x 8.0MP Mini Bullet (VSIP8MPFBMINIIR)	8 x 8.0MP Mini Dome (VSIP8MPVDMINIIRC) 8 x 8.0MP Mini Bullet (VSIP8MPFBMINIIR)	
	Installed HDD Size	4TB	8TB	12TB	
Display	Video Output	1 x HDMI, 1 x VGA		2 x HDMI, 1 x VGA	
	Display Resolution	Configurable from 3840 x 2160 to 1024 x 768			
	Display Split	1/4	1/4/8/9	1/4/8/9/16	
Recording	Recording Resolution	Configurable from 8.0MP (3840 x 2160) to CIF (352 x 288)	Configurable from 12.0MP (4000 x 3000) to CIF (352 x 288)		
	Incoming Bandwidth	200Mbps	320Mbps		
	Video Compression	H.265 / H.264	H.265 / H.264 / MJPEG / MPEG4		
	Bit Rate	16kbps ~ 20Mbps per channel			
Features	Alarm Input / Output	4 channels input / 2 channels relay output (N.O/N.C)		16 channels input / 6 channels relay output (N.O/N.C)	
	Playback Sync	1/4	1/4/9	1/4/9/16	
	Backup Modes	USB Device / Network		USB Device / Network / eSATA Device / Internal SATA burner	
Network	Ethernet	1 x RJ-45 port (10/100/1000Mbps)			
	Power over Ethernet	4 ports (IEEE802.3at/af)	8 ports (IEEE802.3at/af)	16 ports (IEEE802.3at/af)	
	Network Functions	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search, P2P			
	Remote View	iOS (iPhone, iPad) / Android devices / Windows Phone* (limited functionality)			
Storage	Internal HDD	2 x SATA ports, up to 20TB		4 x SATA ports, up to 40TB	
	HDD Modes	Single (no RAID compatibility)			
	USB Interface	2 ports: Rear USB3.0 / Front USB2.0		3 ports: Rear USB3.0 / Front USB2.0	
	Auxiliary Inputs	N/A	1 x RS232 / 1 x RS485	1 x RS232 / 1 x RS485 / 1 x eSATA	
Environment	Power Supply	48VDC / 2A	100 ~ 240VAC, 50 ~ 60Hz		
	Power Consumption	< 9W (without HDD)	< 14.5W (without HDD)	< 17.5W (without HDD)	
	Operating Environment	-10 ~ 55°C / 10 ~ 90%RH / 86 ~ 106kpa			
	Dimensions / Rack Units	375 x 282 x 56mm / 1U	375 x 328 x 53mm / 1U	440 x 411 x 76mm / 1.5U	
	Weight	1.60kg (without HDD)	2.60kg (without HDD)	4.65kg (without HDD)	
Application	Included Cabling				
		CAT5 cabling: 2 x 10m, 1 x 20m, 1 x 30m CAT5 patch cable for networking: 1 x 1.5m 1 x HDMI cable for high definition video output 1 x NVR Remote 1 x Mouse	CAT5 cabling: 4 x 10m, 2 x 20m, 2 x 30m CAT5 patch cable for networking: 1 x 1.5m 1 x HDMI cable for high definition video output 1 x NVR Remote 1 x Mouse	CAT5 cabling: 8 x 10m, 4 x 20m, 4 x 30m CAT5 patch cable for networking: 1 x 1.5m 1 x HDMI cable for high definition video output 1 x NVR Remote 1 x Mouse	
Camera	Camera	8.0MP Mini Dome (VSIP8MPVDMINIIRC)		8.0MP Mini Bullet (VSIP8MPFBMINIIR)	
	Image Sensor	1/2.5" 8.0MP Progressive Scan CMOS			
	Lens	4mm F2.0 Fixed Lens, Horizontal: 87°, Vertical: 48°		4mm F1.6 Fixed Lens, Horizontal: 87°, Vertical: 48°	
	Infrared Range	50m		40m	
	Lighting Compensation	BLC / HLC / DWDR			
	Resolution	8.0MP (3840 x 2160) to CIF (352 x 288)			
	Frame Rate	Main	8.0MP (1~15fps) / 3.0MP (1~25fps)		
		Sub	D1 (1 ~ 25fps)		
		Third	720p (1 ~ 25fps)		
	Audio Input	Built-in Microphone / Compression: G.711a, G.711Mu, AAC, G.726		N/A	
Smart Functions	Tripwire, Intrusion, Object Abandoned/Missing, Face Detection, Motion Detection (4 zones), Region of Interest (4 zones), Privacy Masking (4 zones), Smart Infrared				
Power	12VDC / PoE (802.3af) (Class 0), <5W consumption		12VDC / PoE (802.3af) (Class 0), <7W consumption		

Your local VIP Vision™ IP solutions professional: