

4.0
MEGAPIXEL



Motorised CCTV solutions.

Professional Series: 4.0MP Surveillance Kits available with 4, 8 & 16 motorised cameras

VIP Vision™ Professional Series CCTV kits offer broadcast-quality image performance with built-in Power over Ethernet for fast installations. Mix & match any equivalent priced dome or bullet camera to suit your installation needs.

- Records 4.0MP (2688 x 1520) up to real-time 25fps
 - 4.0MP True WDR 40m IR motorised dome cameras
 - 4.0MP True WDR 60m IR motorised bullet cameras
 - Motorised lens adjustable with buttons or via NVR
 - Remote view in seconds with setup via QR code
 - HDMI & VGA simultaneous video output
 - Built-in Power over Ethernet
 - Pre-installed 1TB/2TB/4TB surveillance grade HDD
 - Remote view for iOS, Android & Windows Phone
- *Camera cabling sold separately*



Beyond Full HD Recording & Live View



Adjustable Motorised Lens



Comprehensive Remote View

Choose from three comprehensive, ready to install packages.

The VIP Vision Professional Series offers complete 4, 8 and 16 channel network surveillance packages, purpose-built for rapid installation and impressive results.



Channel	NVR Model	NVR Description	Camera Description	Accessories
4 Channel	NVRKIT-P441M	4 Channel Professional NVR <ul style="list-style-type: none"> 4 port Power over Ethernet NVR Records 4.0MP at 25fps Pre-installed 1TB hard disk drive (additional backup via USB device or network) 	4 x 4.0MP Motorised Cameras <ul style="list-style-type: none"> 2 x bullet and 2 x dome cameras 2.7 ~ 13.5mm (104°~28°) motorised lens Stream up to 4.0MP (2688 x 1520)IP67 rated metal housing for outdoor use 	Accessories <ul style="list-style-type: none"> CAT5 patch cable for networking: 1 x 1.5m HDMI output cable: 1 x 1m 1 x NVR Remote and 1 x Mouse Camera cabling sold separately
8 Channel	NVRKIT-P842M	8 Channel Professional NVR <ul style="list-style-type: none"> 8 port Extended Power over Ethernet NVR Records 4.0MP at 25fps Pre-installed 2TB hard disk drive (additional backup via USB device or network) 	8 x 4.0MP Motorised Cameras <ul style="list-style-type: none"> 4 x bullet and 4 x dome cameras 2.7 ~ 13.5mm (104°~28°) motorised lens Stream up to 4.0MP (2688 x 1520) IP67 rated metal housing for outdoor use 	Accessories <ul style="list-style-type: none"> CAT5 patch cable for networking: 1 x 1.5m HDMI output cable: 1 x 1m 1 x NVR Remote and 1 x Mouse Camera cabling sold separately
16 Channel	NVRKIT-P1644M	16 Channel Professional NVR <ul style="list-style-type: none"> 16 port Extended Power over Ethernet NVR Records 4.0MP at 25fps Pre-installed 4TB hard disk drive (additional backup via USB device or network) 	16 x 4.0MP Motorised Cameras <ul style="list-style-type: none"> 8 x bullet and 8 x dome cameras 2.7 ~ 13.5mm (104°~28°) motorised lens Stream up to 4.0MP (2688 x 1520) IP67 rated metal housing for outdoor use 	Accessories <ul style="list-style-type: none"> CAT5 patch cable for networking: 1 x 1.5m HDMI output cable: 1 x 1m 1 x NVR Remote and 1 x Mouse Camera cabling sold separately

Technical Specifications

For full specifications and bracket compatibility, please see the individual unit web entry or datasheet.

NVR Model	NVR4PRO3	NVR8PRO7	NVR16PRO7
Product Image			
Video Input	4 channel	8 channel	16 channel
Two-way Talk	1 channel input / 1 channel output / RCA		
Video Output	1 x HDMI / 1 x VGA	1 x HDMI / 1 x VGA	2 x HDMI / 2 x VGA
Maximum Resolution	Configurable from 8.0MP (3840 x 2160) to CIF	Configurable from 12.0MP (4000 x 3000) to CIF (352 x 288)	
Incoming Bandwidth	200Mbps	320Mbps	
Video Compression	H.265 / H.264	H.265 / H.264 / MJPEG / MPEG4	
Bit Rate	16 ~ 20Mbps per channel		
Alarm Input / Output	4 channels input / 2 channels relay output	4 channels input / 2 channels relay output	16 channels input / 6 channels relay output
Internal HDD	2 x SATA ports, up to 10TB each (1TB pre-installed)	2 x SATA ports, up to 10TB each (2TB pre-installed)	4 x SATA ports, up to 10TB each (4TB pre-installed)
Power Supply	48VDC, 2A	100 ~ 240VAC, 50 ~ 60Hz	

Camera Model	VSIPP-4DIRMD	VSIPP-4BIRMG
Image Sensor	1/3" 4.0MP Progressive Scan Exmor CMOS	
Lens	2.7 ~ 13.5mm F1.4 Motorised Varifocal Lens with Fixed Iris	
Min. Illumination	0.008 Lux/F1.5 (Color), 0 Lux/F1.4 (IR on)	
Infrared Range	40m	60m
Lighting Compensation	BLC / HLC / WDR (120dB)	
Resolution	4.0MP (2688 x 1520) to CIF (352 x 288) / Frame Rate: 4.0MP (1 ~ 20fps) / 3.0MP (1 ~ 25fps), Sub: D1 (1 ~ 25fps), Third: N/A	
Smart Functions	Motion Detection (4 zones), Region of Interest (4 zones), Privacy Masking (4 zones), Smart Infrared	
Weather/Vandal Resist	IP67, IK10	IP67
Power Input	12VDC / PoE (802.3af)	

Your local VIP Vision™ IP surveillance professional: