



CCTV that can go anywhere.

Watchguard™ Reolink Go 1080p wireless 4G bullet camera

The Watchguard™ Reolink Go is a wireless CCTV solution that operates on the 4G network, allowing it to be installed anywhere. Enjoy hassle-free installations at any location with no wiring, power supply or WiFi access required.

- Stream up to Full HD / 1080p (1920 x 1080) at 15fps
- Fixed lens with wide 110° diagonal viewing angle
- 10m IR & spotlight; capture details in low light
- Two way talk with built-in microphone & speaker
- Smart PIR motion sensor, with up to 10m range
- IP65 rated weather resistant housing for outdoors
- Non-stop power with solar panel (*sold separately*)
- View footage & receive alerts via the free Reolink app



Full HD Image Resolution



Weather Resistant Housing



Remote View Anywhere



Install Anywhere

100% wireless and portable, install around homes, offices and more



4G or WiFi

Operates on the 4G mobile network when WiFi isn't available * SIM card Required



Solar Powered

Connect the camera to the solar panel for non-stop power (sold separately)



Remote View

Live view footage, 2 way talk, receive alerts & more via smartphone

Specifications		Watchguard™ Reolink 1080p wireless 4G fixed lens bullet	
Product Image			
Ordering Information		REO-GO: Reolink Camera	
Camera	Image Sensor	Starlight CMOS Image Sensor	
	Effective Pixels	1920 (H) x 1080 (V)	
	Infrared System	10m range	
Lens	Lens / Iris	Fixed Lens (6x Digital Zoom)	
	Field of View	Diagonal: 110°	
	Focus	Fixed	
Video	Resolution	1080p / 2.0MP (1920 x 1080)	
	Frame Rate	Main	1080p (1 ~ 15fps)
		Sub	N/A
		Third	N/A
Video Compression	H.264		
IVS	Intelligent Functions	Adjustable PIR motion detection distance up to 10m, 120°(H) PIR detecting angle	
3G/4G Bandwidth	Frequency Bandwidth	LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28 LTE TDD: B40 WCDMA: B1/B2/B5/B8	
	Transmission Data	LTE FDD: Max 10Mbps (DL), Max 5Mbps (UL) LTE TDD: Max 8.96Mbps (DL), Max 3.1Mbps (UL) HSPA+: Max 42Mbps (DL), Max 5.76Mbps (UL) UMTS: Max 384Kbps (DL), Max 384Kbps (UL)	
Interface	Audio Interface	High quality speaker & microphone	
	Audio Alerts	Customise voice recordable alerts	
	Other Alerts	Instant email alerts and push notifications	
	Local Storage	Supports up to 64GB micro SD card	
	Cloud Storage	Supports Reolink Cloud	
Environmental	Battery	7800mAh rechargeable battery (Battery life varies based on settings, usage and temperature)	
	Solar	Can be powered by Reolink solar panels (sold separately)	
	DC Power	Can be powered by 5V/2A power adapter	
	Weather Resistance	IP65	
	Operating Conditions	-10°C ~ 55°C	
	Dimensions	Ø75mm x 113mm	
	Net Weight	0.38kg	
	Included Accessories	1 x Reolink Bullet Camera, 1 x Mount, 1 x Rechargeable Battery, 1 x Pack of Screws, 1 x Reset Needle, 1 x Surveillance Sign, 1 x Mounting Template, 1 x Micro USB Cable, 1 x Quick Start Guide, 1 x Camouflage Skin	

Your local Watchguard™ professional: