



# 1080p plus audio & infrared.

**Mobile Series: Full HD 1080p HDCVI mobile surveillance cameras in 2.0MP**

Keep every angle of your vehicle covered with Mobile Series surveillance cameras from Securview. Choose from vandal dome, compact dome & bumper cameras, capable of Full HD streaming in durable IP67 rated housings.

- Stream 2.0MP / Full HD 1080p (1920 x 1080) 25fps
- Fixed lens, available in 111° to 83° viewing angles
- Smart infrared illumination, up to 20m range
- Built-in microphone mobile series models available
- IP67 weather resistant metal housings (all models)
- Shock resistant housings with aviation connectors
- **DIRFT dome:** Low profile & IK10 vandal resistant
- **DIRAT dome:** Smaller than a tennis ball Ø62 x 62mm
- **CIRAT camera:** Ideal for bumper placement
- **BT camera:** Ideal for flush mount in-bumper



**Built-in Mic Models Available**



**20m Infrared and low light vision**



**IP67 Rated Across the Range**

Model	VSCVI2MPVDIRFTV2	VSCVI2MPDIRAT	VSCVI2MPCIRAT	VSCVI2MPBT2.8	
General					
	Camera Style	Mobile Wedge Dome	Mobile Dome Camera	Mobile Bumper Camera	Mobile Bullet Camera
	Image Sensor	1/2.8" 2.1 Megapixel CMOS		1/2.9" 2.0 Megapixel CMOS	
	Effective Pixels	1937 (H) x 1097 (V)		1920 (H) x 1080 (V)	
	Signal Noise Ratio	> 65dB			
Camera	Lens	2.8mm F1.6 Fixed Lens	3.6mm F2.0 Fixed Lens	3.6mm F2.0 Fixed Lens	2.8mm F2.0 Fixed Lens
	Angle of View	111°	83°	83°	109°
	Focus	Fixed	Fixed / 0.8m Min. Focus Distance	Fixed / 0.8m Min. Focus Distance	Fixed / 0.5m Min. Focus Distance
	Minimum Illumination	0.005 Lux F1.6 (Colour) / 0 Lux IR Active	0.02 Lux at F2.0 (Colour) / 0 Lux IR Active	0.02 Lux at F2.0 (Colour) / 0 Lux IR Active	0.02 Lux F2.0 (Colour) / 0.002 Lux (B/W)
	Electronic Shutter	1/4 ~ 1/100,000s		1/25 ~ 1/100,000s	
	Day/Night	Auto (ICR) / Manual			
	Infrared Range	20m	20m	20m	N/A
	White Balance	Auto / Manual			
	Noise Reduction	2D / 3D	2D		
	Gain Control	Auto			
	Lighting Compensation	BLC / HLC / WDR (120dB)	BLC / HLC / DWDR		
	Video	Resolution	1080p (1920 x 1080) to CIF (352 x 288)		
Frame Rate		25fps (1080p and lower)			
Transmission Distance		3m / 6m / 12m / 18m heavy duty cables available			
Interface	Audio Input	N/A	Built-in microphone	Built-in microphone	N/A
	Alarm Interface	N/A			
	Video Output	1x BNC HDCVI output			
	OSD Menu	Support			
Environmental	Ingress Protection	IP67			
	Vandal Resistant	IK10	N/A		
	Housing	Metal, Polycarbonate	Metal		
	Power Input	12VDC			
	Power Consumption	<2.4W	<2.9W	<2.9W	<0.6W
	Dimensions	Ø106 x 50mm	Ø62 x 62mm	107 x 43 x 55mm	Ø30 x 68mm
	Weight	0.31kg	0.16kg	0.31kg	0.07kg
	Operating Environment	-40° to 60°C / RH90% (max)		-40° to 70°C / RH90% (max)	
Accessories	Product Diagram				
	Compatible Brackets	<p>Mobile Shield (VSBKTA201W) Junction Box (VSBKTA139)</p>			

Your local Securview™ HDCVI solutions professional: