

# Perfect intercom upgrades.

## 2-Wire Hybrid Series: Upgrade existing analogue and 2-wire intercoms

VIP Vision<sup>™</sup> 2-wire residential video intercoms are the perfect upgrade solution to your old intercom or door bell system. Perform incredibly fast upgrades using existing 2-wire infrastructure, without the need for any configuration. Optionally, connect the system to the Internet via the WiFi monitor for remote view and operation.

- 2.0MP wide angle door camera with IR illuminator
- Door stations calls all programmed indoor monitors
- Interfaces with most electric door strikes/mag. locks
- IP65 & IK07 front panel of camera w/ tamper switch
- 7" capacitive touchscreen indoor intercom monitor
- Visitors can leave video messages for unanswered calls (intercom monitor SD card required)
- WiFi monitor for remote monitoring via the app



#### 2-Wire Series | Series Specifications

	Model	INTRDS-H
General	Product Image	
	Main Processor	Embedded Processor
	Backlit Interface	N/A
	Card Support	N/A
	Tamper Detection	Yes
	Camera System	1/2.8" 2.0 MP CMOS HDR Camera Horizontal FoV: 110° ; Vertical FoV: 60°
ā	Video Resolution	960 (H) x 576 (V) @25fps
Camera	Audio Input	1
Ű	Audio Output	Built-in Loudspeaker
	Bidirectional Talk	Support
	Network Protocol	TCP/IP
Environmental	Vandal Resistant	IK07
	Ingress Protection	IP65
	Installation	Flush Mount;Surface Mount
vire	Power Input	via INTCON-H Controller
Ъ	Power Consumption	$\leq$ 1.5 W (standby), $\leq$ 10 W (working)
	Weight / Dimensions	0.502kg / 130 x 96 x 28.5mm
Accessories		96.0 mm
	1300	
		State and a state

### VIP Vision<sup>™</sup> 2-Wire Intercom Kit

Model: INTKIT-H

The INTKIT-H offers everything you need to setup a single door camera & indoor monitor over existing 2-wire cabling, and connect to the internet for remote view.

#### **INTKIT-H inclusions:**

- 1 x INTRDS-H: 2.0MP Intercom Door Station
- 1 x INTMON-H: 7" Touchscreen Indoor Monitor
- 1 x INTCON-H: 1 x 2-wire Input Module with 1 x Extender Module and 1 x Terminating Modules
- 1 x INTIPRDSGSB: Door Station Surface Mount
- 1 x Alarm I/O leads & DC plug-to-2-wire lead
- 1 x Mounting kits for door station & monitor
- 1 x 48VDC Power Supply

Your local VIP Vision<sup>™</sup> Intercom solutions professional:

	Model	INTMON-H
	Product Image	EfAb
	Main Processor	Embedded Processor
-	Video Compression	H.264
Monitor	Audio Input/Output	1 input ; Built in Loudspeaker
Νo	Audio Bit Rate	16 kHz; 16 bit
	<b>Bidirectional Talk</b>	Half-Duplex with Door Station; Full-Duplex with App
	Display Size	7" Colour TFT LCD
	<b>Display Resolution</b>	1024 (H) x 600 (V)
	Alarm Support	6 Input channels / 1 output channel / 1 x RS485
	Operational Input	Capacitive Touchscreen
	Internal Capacity	Up to 64GB MicroSD Card (sold seperately)
	Wi-Fi	IEEE802.11b/802.11g/802.11n
	Network Protocol	IPv4; UDP; DNS; TCP
tal	Operating Temperature	-10 °C to +55°C
nen	Installation	Surface wall mounting bracket & kit
ronr	Power Output	1 (12 V, 200 mA)
Environmental	Power Consumption	$\leq$ 2.5 W (standby), $\leq$ 10 W(working)
ш	Weight / Dimensions	0.633kg / 130 × 189 × 23.9 mm
	mm	
Accessories	-	

