FLASHVIEW^{**}



Purpose-built for 24/7 display.

LCD-U Series: Surveillance grade Ultra HD IPS monitors, available in 27'

Flashview LCD-U series monitors are built for 24/7 continuous video displays used in surveillance applications. They are affordable and reliable, offering up to Ultra HD 4K display resolution, support for audio and wide viewing angles. They also interface well with wall brackets for use in a variety of applications.

- Ultra HD resolution displays in 27"
- Adaptive sync to prevent image lagging
- 5ms low response time for smooth operation
- VESA 100m wall mountable

- Supports display port and HDMI video inputs
- 1x audio output & 2x built-in 2W stereo speakers
- In-plane switching LCD panel technology
- Extra wide viewing angles 178° (H) x 178° (V)



Ultra HD 4K Resolution



Surveillance Grade Displays



Speakers or Audio Output

FLASHVIEW^{**}

LCD-U Series | Specifications

Bypericitations 2/* Ora HD //E CU Monitor Model CDP 127/U Streen Size 27 (nch Appect Ratio 16-3 Resolution 4K (3840-2760, Una +DD, 8.0MP) LCD Panel Type 195 (nc plane Switching) Brightess / Luminace 330 nts Display Goldur 88 in + FRC Viewing Angles 178 (PL / 1787 (V) Response Thme 50% Refera Rate 60½2 Other Input 1 x Display Fold, x HDMI Port Orientation 400 comput Refera Rate 60½2 Rower Input 1 x Display Fold, x HDMI Port Orientation 2 x 2// Speakers, 1 x Audio Oxput Power Input 1 2002 (A), 50% (standwd) 48W (max) VISA 100mm Title Adjustment Vis Operating Temperature 0		
Screen Size 27 Inch Appect Natio 199 Resolution 4K (3801x 2160, Una +10, 8.0MP) LED Panel Type 195 (In-plane Switching) Brightness / Luminance 350 n/s Contrast Ratio 1000.1 Disply Colour 881 + FRC Versing Angeles 70 n/s Wording Angeles 70 n/s Wide Input 1.2 Display Port, 2 x HDMI Versing Angeles 70 n/s Orgen Time 50 n/s Befersh Rate 664r2 Vides Input 1.2 Display Port, 2 x HDMI Versing Angeles 70 n/s Orgen Torientation Wereight Input Audio Support 72 N/s Vides Input 120PC 4A, 20.5W (standby) 39W (standby) 48W (max) Vides Input 120PC 4A, 20.5W (standby) 39W (standby) 48W (max) Vides Input 120PC 4A, 20.5W (standby) 39W (standby) 48W (standburd, 48W (max) Vides Input 120PC 4A, 20.5W (standby) 39W (standburd, 48W (max) Vides Input 0/C - 40°C, <0/05H Display Input 0/C - 40°C, <0/05H Included Accesco	Specifications Model	27" Utra HD IPS LCD Monitor
Apect Ratio 169 Resolution 4K (3840 x 2166, United), 8.00P) Big Resolution KK (3840 x 2166, United), 8.00P) Big Resolution IS Diplane Solution Big Resolution Solution Big Resolution Solution Big Resolution Solution Double Solution Solution		
Verong Advices Contrast Ratio State ICD Panel Type ISO Panel Syne State		
CD Panel Type IPS (In-plane Switching) Bit of platess / Luminance 350 mls Contrast Ratio 10001 Display Colour 8 Bit + FRC Viewing Angles 178* (Hy) / 178* (V) Response Time 6 Orbita X Viewing Angles 5 nits Response Time 6 Orbita X Viewing Angles 1 x Display Port 2 x HOM Port Orientation Viewing Angles Port Orientation 2 x 22V Speakers, 1 x Audio Output Port Orientation 2 x 22V Speakers, 1 x Audio Output Port Orientation 2 x 22V Speakers, 1 x Audio Output Port Orientation 1 200C 4A, 50.5W (standay) 30W (max) Time 5 Orbita Microw Mic	-	
Brightness / Luminance 350 nils Officiant Ratio 1000-1 Display Colour 814 + FRC Viewing Angles 178* 00 / 178* (V) Response Time 5ms Refersh Rate 60 hz Viewing Angles 1 x Display Fort, 2 x HDMI Port Orientation Vertral Input Audio Support 2 x 2W Speakers, 1 x Audio Output Port Orientation Vertral Input Audio Support 2 x 2W Speakers, 1 x Audio Output VEXA 1000mm View Input 1 200C 4A, c0.5W (analtry) 30W (standard) 48W (max) VESA 100mm View Input 0C-40°C, <50% BH Dimensions 614mm x 463mm x 216mm (with base), 614mm x 368mm x 49mm (without base) Net Weight 4.5kg Included Accessories HDMI cable, power adapter, monitor base		
Unify Colour 8 Bit + FRC Newing Angles 178' (H) / 178' (V) Response Time 000000000000000000000000000000000000		
Unify Colour 8 Bit + FRC Newing Angles 178' (H) / 178' (V) Response Time 000000000000000000000000000000000000	Contrast Ratio	
Versing Angles 178° (H) / 178° (V) Refresh Rate 5ms 1000 60Hz 1010 1 x Display Port, 2 x HDMI Versing Angles 00Hz 1010 1 x Display Port, 2 x HDMI Versing Angles 00Hz 1010 1 x Display Port, 2 x HDMI Versing Angles Versing Angles 1010 1 x Display Port, 2 x HDMI Versing Angles Versing Angles 1010 1 x Display Port, 2 x HDMI 1010 1 x Display Port, 2 x H		
Response Time Sms Refersh Rate 60Hz Ideo Ioput 1 x Dolghy Port 2 x DDMI Port Orientation Vertical Input Addo Support 2 x 220 Speakers, 1 x Audio Output Power Input 0 2000/00000000000000000000000000000000		
Refresh Rate 60Hz 901 Port Orientation 1 x Display Port, 2 x H DMI Port Orientation 2 x 2W Spokers, 1 x Audio Output Port Orientation 2 x 2W Spokers, 1 x Audio Output Port Orientation 2 x 2W Spokers, 1 x Audio Output Port Orientation 1 2002 4A, e 0.5W (standard) 48W (max) VESA 100mm Tit Adjustment Ves Demanions 614mm x 463mm x 216mm (with base), 614mm x 386mm x 49mm (without base) Net Weight -4.5kg Included Accessories HDMI cable, power adapter, monitor base		
Port Orientation Vertical Input Audio Support 2 x 2W Speakers, 1 x Audio Output Power Input 12VDC 4A, c05W (standbr) 48W (max) VESA 10mm Tilt Adjustment 0°C-40°C, c05W (standbr) 48W (max) Dimensions 614mm x 463mm x 216mm (with base), 614mm x 368mm x 49mm (without base) Net Weight 4.5kg Included Accessories HDMI cable, power adapter, monitor base Product Diagrams 		
Vertical Input Vertical Input Audio Support 2 x 2W Speakers, 1x Audio Output Power Input 12/DIC 4A, 0.5W (standio) 48W (max) VESA 100mm Tit Adjustment 0°cr-40°c, s09WBH Dimensions 614mm x 463mm x 216mm (with base), 614mm x 368mm x 49mm (without base) Net Weight 4.5kg Included Accessories HDMI cable, power adapter, monitor base Verture Diagrams Image: Standing Stan	ଥ Video Input	1 x Display Port, 2 x HDMI
TATU Guidancy 1 Power input 12VDC 4A, 6.5W (standby) 30W (standby) 48W (max) Power input 12VDC 4A, 6.5W (standby) 30W (standby)	Port Orientation	
VESA 100mm Tilt Adjustment Yes Dimensions 0°C-40°C, 400°C,	별 Audio Support	
Til Adjustment Yes Operating Temperature 0°C-40°C, < 290%RH Dimensions 614mm x 463mm x 216mm (with base), 614mm x 356mm x 49mm (without base) Net Weight 4.5kg Included Accessories HDMI cable, power adapter, monitor base	Power Input	12VDC 4A, ≤0.5W (standby) 30W (standard) 48W (max)
Operating Temperature 0%-40%, <90%RH	VESA	100mm
Organity A dominant A do	Tilt Adjustment	Yes
Organity A dominant A do	Operating Temperature	0°C~40°C, <90%RH
Included Accessories HDMI cable, power adapter, monitor base Product Diagrams	[©] Dimensions	614mm x 463mm x 216mm (with base), 614mm x 368mm x 49mm (without base)
Product Diagrams	Net Weight	
Product Diagrams	Included Accessories	HDMI cable, power adapter, monitor base
	Product Diagrams	

T

Your local Flashview professional: