



For multi-dwelling buildings.

Apartment Series: IP/2-wire IP intercom door station with 2.0MP camera

This intercom door station from the VIP Vision Apartment Series can improve access and communication in multi-dwelling premises. It features support for intercom upgrades via existing 2-wire infrastructure and for new IP installations. It features keypad or IC card unlock for easy access.

- 1/2.9" 2.0MP sensor, 1080p Full HD resolution
- Wide angle lens with 140° horizontal field of view
- Keypad for code unlock & NFC reader for card access
- Connect up to 200 intercom monitor(s) via Ethernet
- Intuitive, easy-to-use mechanical button interface
- 48VDC / PoE (802.3af/at) power input support
- IP65/IK08 weather & vandal resistant front plate
- Backlit OLED interface & supplemental white light



Connect up to 200 Indoor Monitors



Calls Independent Dwellings



Weather & Vandal Resistant

Apartment Door Station | Series Specifications

Model		INTIPADSD2
General	Main Processor	Embedded Microprocessor
	Low Light Visibility	Backlit 2.3" OLED, Supplemental White Light (AGC)
	Interface	1 x RJ45, 1 x 12V/600mA, 1 x Alarm I/O, 1 x Wiegand, 1 x RS-485, 1 x Door Chime, 1 x Exit Button, 1 x Lock Control
	Card Support	Mifare, Up to 30mm card detection, AM Modulation, 13.56MHz, 42dBuA/m@10m max. TX power
	Camera System	1/2.9" 2.0 Megapixel CMOS with 2mm lens (Horizontal. FoV: 140°)
	Audio Input	Omni-directional Microphone
	Audio Output	Embedded Loudspeaker
	Bidirectional Talk	Support
	Additional Storage	MicroSD Slot, up to 256GB (sold separately)
	Ethernet	10M/100Mbps Self-adaptive
	Network Protocol	TCP/IP
	Max. Additional Door Stations	20
	Max. Indoor Monitors	500
	App Connection	N/A
Environmental	Vandal Resistant	IK08
	Tamper Detection	Yes
	Ingress Protection	IP65 (Front plate only, silicone sealant required during installation)
	Installation	Surface Mount / Flush Mount (sold separately)
	Power Input	48VDC (Power supply sold separately), PoE (802.3af/at)
	Power Consumption	Standby <5W / Operation <7W
	Operating Environment	-40°C ~ +60°, 10~90% relative humidity
	Dimensions	200 x 98 x 35mm
	Weight	0.66kg
	Accessories	Product Diagram
Compatible Brackets		<p style="text-align: center;">Flush Mount (INTIPADSDFB) / Surface Mount (INTIPADSDSB)</p>

Your local VIP Vision™ IP solutions professional:

Apartment Series Example IP Installation | System Map

This diagram demonstrates a system with one front gate door station, one apartment complex door station, monitors for each apartment and a management centre. The system can integrate up to 500 indoor monitors and 20 additional intercom door stations.

This diagram is for IP installations.

