



HD surveillance made easy.

Professional 8 Channel IP Surveillance Kit

Model: NVR8PROPACK4HD

- Records 2.0MP (1920 x 1080) at 25fps real-time
- 4 x 2.0MP True WDR 50m IR IP67 mini-domes
- 4 x 2.0MP True WDR 40m IR IP67 mini-bullets
- Remote view in seconds with setup via QR code
- HDMI & VGA simultaneous video output
- Built-in 8 port Power over Ethernet (PoE)
- Pre-installed 2TB surveillance hard disk drive
- Remote view for iOS, Android & Windows Phone



Professional 8 Channel IP Surveillance Kit

Model: NVR8PROPACK4HD



Package Includes

- VIP Vision™ 8 Channel Professional NVR with built in PoE
- Pre-installed 2TB surveillance hard disk drive
- 4 x 2.0MP 50m infrared weather resistant metal dome cameras
- 4 x 2.0MP 40m infrared weather resistant metal bullet cameras
- CAT5 cabling for cameras: 4 x 10m, 2 x 20m, 2 x 30m
- CAT5 patch cable for networking: 1 x 1.5m

Product Overview

The VIP Vision NVR8PROPACK4HD is a complete 8 channel network surveillance system, built for rapid installation and impressive results. It is an ideal CCTV package for business and residential applications, especially in small retail environments.

It is easy to achieve excellent high definition security, up to 2.0 megapixel resolution at 25fps, with the NVR8PROPACK4HD. Connecting cameras is performed quickly thanks to the built-in 8 port power over Ethernet switch and included pre-terminated CAT5 cables.

This kit comes with a pre-installed 2TB surveillance-grade hard drive, providing reliable footage storage and faster installation. Footage can also be exported via USB device or over the network.

Enabling remote view is just as simple as installation with the QR code configuration tool. Simply connect the NVR to the Internet and scan the QR code with your smartphone to automatically configure remote view on your device. Remote view compatible with iOS, Android and Windows Phone. QR code for iOS and Android only.

Model	NVR8PRO4
System	
Main Processor	Dual-core embedded processor
Operating System	Embedded Linux
Video Input	8 channel
Two-way Talk	1 channel input / 1 channel output / RCA
ONVIF Conformance	2.4 Conformance
Display	
Video Output	HDMI / VGA
Resolution	Configurable from 3840 x 2160 to 1024 x 768
Display Split	1/4/8/9
OSD	Camera title, Time, Video loss, Camera lock, Motion detection
Recording	
Video Compression	H.265 / H.264 / MJPEG
Maximum Resolution	Configurable from 12.0MP(4000 x 3000) to CIF (352 x 288)
Incoming Bandwidth	256Mbps
Bit Rate	1 ~ 20Mbps
Detection	
Alarm Input / Output	8 channels input / 3 channels relay output
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer
Video Detection	Motion (Zones: 396(22x 18)), Video Loss, Camera Blank
Playback & Backup	
Playback Sync	1/4/9
Search Modes	Time/Date, Alarm, By Motion, Exact search, Smart search
Backup Modes	USB Device / Network / Internal SATA burner
Network	
Ethernet	1 RJ-45 port (10/100/1000M)
Power over Ethernet	8 ports (IEEE802.3af)
Max. User Access	128 users
Remote View	iOS (iPhone, iPad) / Android devices / Windows Phone
Storage	
Internal HDD	2 SATA ports, up to 12TB
Auxiliary	
USB Interface	2 ports: Rear USB3.0 / Front USB2.0
Auxiliary Inputs	1 x RS232 / 1 x RS485
General	
Power Supply	100 ~ 240VAC, 50 ~ 60Hz
Operating Environment	-10 ~ 55°C / 10 ~ 90%RH / 86 ~ 106kpa
Dimensions	375 x 275 x 56mm
Weight	2.65kg (without HDD)

Camera Model	VSIP2MPVDMINIIRC3.6	VSIP2MPFBMINIIRV2
Camera		
Camera Type	Mini Dome	Mini Bullet
Image Sensor	1/2.7" 2 Megapixel Progressive Scan CMOS	
Lens	3.6mm F2.0 Fixed Lens (91°)	3.6mm F2.2 Fixed Lens (93°)
Day/Night	Auto (ICR) / Colour / B&W	
Backlight Compensation	BLC / HLC / WDR (120dB)	
Audio Input	N/A	
Maximum Infrared Range	50m	40m
Smart Functions	Tripwire / Intrusion / Abandoned & Missing Object Detection / Scene Change / Face Detection	
Video		
Resolution	Configurable from 2.0MP (1920 x 1080) to CIF (352 x 288)	
Frame Rate	Main	1080p and lower (1 ~ 25fps)
	Sub	D1 and lower (1 ~ 25fps)
	Third	720p and lower (1 ~ 13fps)
Environment		
Ingress Protection	IP67 Weather Resistant	
Vandal Resistant	N/A	
Power Input	12VDC / PoE (802.3af)	

Your local VIP Vision™ professional: